



07 Pearl



12 Storm Grey



14 Karoo Moon



10 Glacier



72 Mirage



77 African Violet



05 Long Beach



38 Fresh Cream



20 Pebble Stone



41 Parchment



70 Fawn



81 Beige



15 Pewter



18 Hard Coal



19 Black



58 Jade



54 Desert Oasis



52 Mint



49 Namib Dawn



22 Coral



28 Life Blood



89 Good Earth



86 Ochre



APPLICATIONS

Domestic, commercial, industrial and public sector

- 1.6 mm - domestic applications
- 2.0 mm - general contract
- 2.5 mm - heavy contract
- 3.2 mm - industrial and forklift applications

- housing/shops and retail outlets / supermarkets office and government buildings / hospitals / schools recreational facilities / warehouses / factories
- heavy pedestrian traffic areas / corridors / entrances utility and storage areas / stores floors / class rooms

INSTALLATION & MAINTENANCE

- Kalahari Quartz general purpose vinyl floor tiles can be installed on any sub-floor that is even, stable, dry and clean.
- Maintenance procedures depends on the type of application, the nature and level of soiling and the standard required.
- Full technical information is available on request.

Kalahari Quartz™

Vinyl Floor Tiles **Solving flooring puzzles**

DESCRIPTION

High Performance, general purpose vinyl floor tiles

- homogeneous through-marbled composition ensures colour and marbling does not wear through
- reinforced with very hard and fine, naturally weathered fillers which ensures:
 - exceptional durability and wear resistance
 - very good dimensional stability
 - high point load and impact resistance
 - good all round chemical resistance
 - exceptional fire resistance (class 1)

FEATURES AND BENEFITS

Proven technology

- International technology with reinforced vinyl semi flexible floor tiles using natural quartz, has been used in access of 30 years or more.

Chemical resistance

- excellent resistance to a wide range of chemicals including acids, alkalis and detergents.

Dimensionally stable

- Kalahari Quartz general purpose vinyl floor tiles are impervious to water and moisture, have a low coefficient of expansion and do not shrink or leach chemicals.

Factory Finish

- Kalahari Quartz general purpose vinyl floor tiles are supplied with a high quality metallised protection polish.
- The top surface treated in this way leaves a pleasant sheen which is easy to maintain.

Tile Format

- Boxes of tiles are easy to handle and transport
- Tiles usually mean less cutting, less waste and more economical use of material as compared to sheet.
- A damaged tile may be easily removed and replaced.

Guarantee

- Kalahari Quartz general purpose vinyl floor tiles may be guaranteed for up to 10 years against wearing out, provided they are specified, installed and maintained in accordance with our recommendations

Kalahari Quartz™

Vinyl Floor Tiles **Solving flooring puzzles**

KALAHARI QUARTZ, 1. SEMI-FLEXIBLE VINYL FLOOR TILES

Technical Specifications

Kalahari Quartz tiles are manufactured in strict accordance with SABS 581:1992 and carry the mark. All processes at Kalahari Floor tiles are carried out in accordance with laid out procedures and have been awarded ISO 9002 status as proof thereof.

Kalahari Quartz tiles have exceptional fire resistance and have been rated as Class 1 under the SABS fire classification.

Recommended Specification

Trade Name specific

Supply and fix 1.6/2.0/2.5/3.2mm x 300 x 300mm Kalahari Quartz quartz reinforced vinyl floor tiles manufactured to SABS Specification 581:1992, laid in an approved water based acrylic adhesive, spread with a notched trowel, on a suitably prepared dry substrate, all in accordance with the manufacturer's specification.

It is essential that the floor tiles must rolled in both directions, after installation, using an articulated 68kgs, three sectional roller.

The newly installed Kalahari Quartz quartz reinforced vinyl tiles should be scrubbed three days after installation with a diluted neutral detergent complying with SABS 825 and thoroughly rinsed. When the floor is dry, apply three coats of a water based floor dressing complying with SABS 1042.

Non Trade Name Specific

Supply and fix 1.6/2.0/2.5/3.2mm x 300 x 300mm quartz reinforced vinyl floor tiles manufactured to SABS Specification 581:1992, laid in an approved water based acrylic adhesive, spread with a notched trowel, on a suitably prepared dry substrate, all in accordance with the manufacturer's specification.

It is essential that the floor tiles must rolled in both directions, after installation, using an articulated 68kg, three sectional, metal floor roller.

The newly installed quartz reinforced vinyl tiles should be scrubbed three days after installation with a diluted neutral detergent complying with SABS 825 and thoroughly rinsed. When the floor is dry, apply three coats of a water based floor dressing complying with SABS 1042.

Product Detail

Guage	1.6mm	2.0mm	2.5mm	3.2mm
Tile size	300x300	300x300	300x300	300x300
Qty/box	60 Tiles	50 Tiles	40 Tiles	30 Tiles
M2/box	5.4	4.5	3.6	2.7
Mass/m2	3.04kg	3.80kg	4.75kg	6.08kg
Mass/box	16.4kg	17.1kg	17.1kg	16.4kg

KALAHARI Q-FLEX, 2. FLEXIBLE VINYL FLOORING

Technical Specifications

Kalahari Q-Flex tiles are manufactured in strict accordance with SABS 786:1992 and carry the mark. All processes at Kalahari Floor Tiles are carried out in accordance with laid out procedures and have been awarded ISO 9002 status as proof thereof.

Kalahari Q-Flex tiles have exceptional fire resistance and have been rated as Class 1 under the SABS fire classification.

Recommended Specification

Trade Name specific

Supply and fix 1.6/2.0/2.5/3.2mm x 300 x 300mm Kalahari Q-Flex reinforced vinyl floor tiles manufactured to SABS Specification 786:1992, laid in an approved water based acrylic adhesive, spread with a notched trowel, on a suitably prepared dry substrate, all in accordance with the manufacturer's specification.

It is essential that the floor tiles must rolled in both directions, after installation, using an articulated 68kgs, three sectional roller.

The newly installed Kalahari Q-Flex reinforced vinyl tiles should be scrubbed three days after installation with a diluted neutral detergent complying with SABS 825 and thoroughly rinsed. When the floor is dry, apply three coats of a water based floor dressing complying with SABS 1042.

Non Trade Name Specific

Supply and fix 1.6/2.0/2.5/3.2mm x 300 x 300mm quartz reinforced vinyl floor tiles manufactured to SABS Specification 786:1992, laid in an approved water based acrylic adhesive, spread with a notched trowel, on a suitably prepared dry substrate, all in accordance with the manufacturer's specification.

It is essential that the floor tiles must rolled in both directions, after installation, using an articulated 68kg, three sectional, metal floor roller.

The newly installed quartz reinforced vinyl tiles should be scrubbed three days after installation with a diluted neutral detergent complying with SABS 825 and thoroughly rinsed. When the floor is dry, apply three coats of a water based floor dressing complying with SABS 1042.

Kalahari Quartz™

Vinyl Floor Tiles **Solving flooring puzzles**

Unit 9, 997 Richards Drive, Midrand
Postnet Suite CP53, Private Bag x 65, Halfway House, 1685
Tel: +27 11 805 9561, Fax: +27 11 805 9563
www.kalahariquartz.co.za

Kalahari Quartz Reinforced Vinyl Flooring